

BF03

油气软管
OIL AND GAS HOSE



型号 TYPE	 内径 I.D		 外径 O.D		 最大工作压力 max W.P		 最小爆破压力 min B.P		 参考重量 W.T
	mm	inch	mm		MPa	Psi	MPa	Psi	
BF03-06-1.5	6	1/4	13.5		1.5	217	6.0	870	0.15
BF03-06-1.5	8	5/16	16		1.5	217	6.0	870	0.21
BF03-10-1.5	10	3/8	18		1.5	217	6.0	870	0.25
BF03-13-1.5	12.5	1/2	21		1.5	217	6.0	870	0.29
BF03-16-1.5	16	5/8	26		1.5	217	6.0	870	0.47
BF03-19-1.5	19	3/4	29		1.5	217	6.0	870	0.53
BF03-25-1.5	25	1	36		1.5	217	6.0	870	0.76
BF03-32-1.5	31.5	1-1/4	44		1.5	217	6.0	870	0.96
BF03-38-1.5	38	1-1/2	51		1.5	217	6.0	870	1.25
BF03-51-1.0	51	2	65		1.0	217	4.0	870	1.7

注：编号后面加“G”代表耐高温高压介质，最高温度为 135°C。示例：BF03G-13-1.5。



结构：

软管由耐油的内胶层、一层纤维编织增强层和耐候的外胶层组成，外观为黑色光面或布纹。

应用：

适用于输送航空煤油、汽油、柴油、油气混合以及其他矿物油类，温度范围为 -40°C ~ +120°C (G 型为 135°C)。

CONSTRUCTION:

This hose shall consist of an oil resistant synthetic rubber, one fiber braid reinforcement and weather resistant smooth or fabric synthetic rubber cover.

APPLICATIONS:

Suitable for jet fuel, gasoline, diesel; mixture of oil and gas and other mineral oil.
Working temperature: -40 °C ~ +120 °C (Type G: up to 135°) .